

KPBasic

End-of-Life Information

Grundfos KPBasic 200, 300 and 600 pumps must be disposed of according to local regulations by using a public or private waste collection service. If this is not possible, contact the nearest Grundfos company or service workshop.

Safety Risk

- Safety related to materials used
There is no risk for people during the disassembly process posed by the materials used for the product.
- Safety related for handling the product
There is no risk for people when handling the product.

Disassembly of the Product

The main materials of the components are:

- Noryl GFN 2
- Stainless steel
- Iron
- Copper

and can therefore be recycled to a large extend – depending on the national possibilities for recycling.

The pump is assembled using screws and bolts and can be disassembled with standard tools. There are no loose parts inside the motor.

Designation	Name	Material	Special Disassembly Consideration
1	Cable	Cable scrap	
2	Float switch	Cable scrap	
3	Top cover	Noryl GFN 2	
4	Nozzle	Rubber, NBR	
5	Capacitor	Electronic scrap	
6	Cover	Stainless steel	
7	Motor unit	Stainless steel, Copper and Aluminium	
8	Housing	Noryl GFN 2	
9	Elbow	Noryl GFN 2	
10	Impeller	Noryl GFN 2	
11	Wear ring disc	Noryl GFN 2	
12	Suction strainer	Noryl GFN 2	
Additional materials:			

